

SETUP SHEET (SIGHT)(S)



				•		
Name: 8IGHT-E 2.0 Race Roller Vehicle	Setup	Date:			Event:	
City:	State:	Track:				
	☐ Hard Packed ☐ Blue Groov ☐ Loose/Loamy ☐ Dry	e 🗆 Wet	□ Low Bite ✓ □ Med Bite	☐ High Bite		
Front Suspension	Differentials		Acker		Bump Steer	
Toe: 2 degrees of toe out	_ Front: ☒ Standard ☐ Smarr	.	Lon	_		
Ride Height: 27mm	_ Spring Wire Dia:		Sho	ort	Up Down	
Camber: -1 degree	_ Qty of Springs:					
Caster: Stock(20 degrees)						3
Sway Bar: 2.3mm	Ramp Plate:					1
	_ Grease:			B A		utaida
Piston/Oil: 54/40wt Losi	_ Diff Fluid: Losi 5000wt		/		.	utside Inside 3
Spring: Silver 4.4lbs	-				9	1
Limiter/Droop: See shock length	_ Center: ☑ Standard ☐ Sm	art				
Overall Shock Length: 95mm	– Spring Wire Dia: ——					
Steering Ackerman: Long	– Qty of Springs:——	I				
Bump Steer: Down	Ramp Plate:					
Camber Link: 2/B	– Grease:		Notes:			
Shock Location: 2/Inside	_ Diff Fluid: Losi 5000w	<u>t</u>	110100.			
Rear Suspension	<u>'</u>					
Toe: 3 degrees						
Anti-Squat: 3 degrees		— F				
Ride Height: 29mm						
Camber: -2 degrees						
Rear Hub Spacing: Back					3— 2—	
Sway Bar: 2.3mm		-		DCB A 	ı	
Piston/Oil: <u>56/25wt Losi</u> Spring: <u>Green 3.1lbs</u>		-				1
Limiter/Droop: See shock length		_			Outside	2 3
Overall Shock Length: 106mm					Inside	
2 /2						
Shock Location: 2/Inside					////	
Rear Diff Fluid: Losi 2000wt						
Power Train			Mata			\ <u>\\</u>
Motor: Xcelorin 2100Kv Ba	ttery: 4S 5000mAh Lipo		Notes:			
Spur: <u>45</u>	(Recommended)					
Pinion: 15						
ESC		Tires	Туре		Camanaund	Insert
Throttle Limit: 0%	_				Compound	
Motor Timing: Normal	_					
Drag Brake: 4%		Rear:				
Braking %: 20%		Notes:				
BEC Voltage: 6.0v						
Initial Acceleration: High						
Neutral Deadband: 3%	_					